



sicaf

COOLING EVOLUTION



MONOBLOCKS AND REFRIGERATED SYSTEMS

COMMERCIAL SPLIT UNITS

Commercial Split Units

Electronic control panel
Expansion by means of thermal expansion valve
Cable for door heater (on low temperature units)
Fixed calibration low pressure switch
High pressure switch on all three-phase units and on single-phase HMM122-152
(in compliance with the "pressure equipment" directive 97/23/CE)
Direct drainage of condensate water with heater
Hermetic compressor
Electric defrost
Filter on the liquid line
Remote control panel connected to the unit with a 5m long cable
Sight glass
All units are equipped with a liquid receiver complying (in compliance with the
"pressure equipment" directive 97/23/CE)
Pre-arrangement for door switch and room light connections



TN +5°C/-5°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

HMM200

Unità Unit Unit	Tensione Voltage Voltage	volt/Hz	400/3/50
	Assorbimento Absorption Absorption	W	2250
	Compressore Compressor Kompressor	m ³ /h	7,57
	Tipo comp. Comp. Type Comp. Type	E/S	E
	Sbrinamento Defrost Defrost	El / Gc	1400
	Refrigerante Coolant Coolant		R452A
Condensatore Condensator Condensator	Ventole Fans Fans	n°x Ø	1x350
	Portata aria Air flow Air flow	m ³ /h	2200
Evaporatore Evaporator Evaporator	Ventole Fans Fans	n°x Ø	3x254
	Portata aria Air flow Air flow	m ³ /h	2350
	Gittata Air-throw Air-throw	m	m.6
Dimensioni Sizes Sizes	Larghezza Width Width	mm	930 (C) / 1470 (E)
	Profondità Depth Depth	mm	790 (C) / 620 (E)
	Altezza Height Height	mm	750 (C) / 390 (E)
	Peso Weight Weight	kg	98 (C) / 40 (E)


TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

		m ³	W
TA +20°C	TC +5°C	74,3	5303
	TC 0°C	61,8	4548
	TC -5°C	48,7	3830
TA +32°C	TC +5°C	62,5	4337
	TC 0°C	50,6	3893
	TC -5°C	37,7	3113
TA +43°C	TC +5°C	46	3724
	TC 0°C	34,5	3139
	TC -5°C	26,6	2592

1


DIMENSIONI | SIZES | ABMESSUNGEN

DATI E CARATTERISTICHE IMBALLO > P. 60
PACKAGING DATA AND FEATURES, PAGE 60
VERPACKUNGSDATEN UND -MERKMALE, SEITE 60



Evaporatore | Evaporator | Verdampfer ↗


Unità | Unit | Einheiten ↘



2


DIMENSIONI | SIZES | ABMESSUNGEN

DATI E CARATTERISTICHE IMBALLO > P. 60
PACKAGING DATA AND FEATURES, PAGE 60
VERPACKUNGSDATEN UND -MERKMALE, SEITE 60



Evaporatore | Evaporator | Verdampfer ↗


Unità | Unit | Einheiten ↘



3


DIMENSIONI | SIZES | ABMESSUNGEN

DATI E CARATTERISTICHE IMBALLO > P. 60
PACKAGING DATA AND FEATURES, PAGE 60
VERPACKUNGSDATEN UND -MERKMALE, SEITE 60



Evaporatore | Evaporator | Verdampfer ↗


Unità | Unit | Einheiten ↘



3M


DIMENSIONI | SIZES | ABMESSUNGEN

DATI E CARATTERISTICHE IMBALLO > P. 60
PACKAGING DATA AND FEATURES, PAGE 60
VERPACKUNGSDATEN UND -MERKMALE, SEITE 60



Evaporatore | Evaporator | Verdampfer ↗


Unità | Unit | Einheiten ↘



4


DIMENSIONI | SIZES | ABMESSUNGEN

DATI E CARATTERISTICHE IMBALLO > P. 60
PACKAGING DATA AND FEATURES, PAGE 60
VERPACKUNGSDATEN UND -MERKMALE, SEITE 60



Evaporatore | Evaporator | Verdampfer ↗


Unità | Unit | Einheiten ↘



5

DIMENSIONI | SIZES | ABMESSUNGEN

DATI E CARATTERISTICHE IMBALLO > P. 60
PACKAGING DATA AND FEATURES, PAGE 60
VERPACKUNGSDATEN UND -MERKMALE, SEITE 60



Evaporatore | Evaporator | Verdampfer ↗

Unità | Unit | Einheiten ↘

